



Level 2 EVSE OCPP AC Charger (80A)

Artemis

High power Level 2 charger delivering up to 19.2kW/80A max at 208/240V via a standard J1772 connector.

Offers flexible charging for high-performance EVs requiring faster charging times.

Quick Facts:

- Level 2 charger, with smart EV charge monitoring & remote management
- LCD screen with charging status display
- **Flexible load balancing:** 12-80A (Up to 19.2kW) charging output
 - Adjustable for remote load balancing via web app
- **For EV Drivers:** QR code user authentication
- **Connectivity:** 4G LTE, WiFi, Ethernet
- **Certifications:** CSA (US and Canada), FCC, CTEP, Energy Star
- **Standards:** NEMA-4, ISO 15118, UL 2231-1, UL 2231-2, UL 2594, UL 1998, UL 991, FCC Part 15 Class B



Compact & Ergonomic

Compact, crescent design, with 23.5° angled connector dock, and 4.3 inch LCD display for charging status. Docking station for clean cable management.

.....



Durable, Electrician Friendly Design

Engineered for durability with IP65-rated dust and water resistance, IK10 impact protection, and concealed screws for anti-theft security. Installation is streamlined with an electrician-friendly step-by-step checklists and guides.

.....



OCPP Enabled, Rigorously Tested

OCPP 1.6J enabled for seamless integration with charging networks. Artemis conforms to UL and FCC standards, is NEMA 4 rated, and meets ISO 15118 requirements for North America.

Level 2 EVSE OCPP AC Charger (80A)

Artemis



Data Sheet

Dimensions	H	W	D
	11" (280mm)	11" (280mm)	5.8" (148mm)
Weight	14.11 lbs (6kg) with cable		
Operating Temperature	-22 to 122°F (-30 to 50°C)		
Electrical Ratings	208/240V, Max 80A (~19.2kW), with the ability to further dial down to 12A (~2.5kW)		
Cable & Connector	25ft (7.5m) length, J1772 connector		
Enclosure Type	NEMA Type 4		
Connectivity	4G LTE, WiFi, Ethernet		